

WS-3490

展开(288x192mm)

CLEANING YOUR HELMET

Use only mild soap and water to clean the helmet, straps and pads. **DO NOT** use chemicals. **DO NOT** use solvents, paints and hydrocarbons.

STORING YOUR HELMET

After each use, allow the helmet to air dry and then store in a cool, dry place. Excessive heat can damage the helmet. In direct sunlight dark gear bags and automobile trunks can get hot enough to cause heat damage. Damaged helmets will appear to have uneven or bubbly surfaces.

CHECK THE FIT

Grab the helmet with both hands and twist it to the left and to the right. If the helmet fits right the skin on the fore head will move as the helmet moves. If it does not, the helmet is too loose. Return to step 1.

CHECK THE STRAP

Grab the helmet with both hands and try to move it by rolling the helmet forward and backwards as far as you can. Make a serious effort. If you can roll it off the head completely in either direction, or roll it forward so far that it blocks vision or backwards far enough to expose the forehead it doesn't fit right. Repeat Steps 3 and 4 until the helmet movement is minimal.

WARNING

If you cannot adjust your helmet to fit as required by Step 5, **DO NOT USE THIS HELMET**. Replace it with a different size.

HELMET INSTRUCTIONS

The helmet you have just purchased provides protection, whether on or off the road. To ensure proper use of this helmet, familiarise yourself with its features, fit and care by carefully reading through this manual before wearing your new helmet.

DO NOT USE HEAT DAMAGED HELMETS

Distributed by:
KMART AUSTRALIA LTD 690 SPRINGVALE ROAD MULGRAVE VIC 3170 AUSTRALIA
KMART NEW ZEALAND REGIONAL OFFICE C/O KMART PAPAETOE STORE
HUNTERS PLAZA, GREAT SOUTH ROAD, PAPAETOE, AUCKLAND, NEW ZEALAND
MADE IN CHINA

PERFORMANCE CYCLING HELMETS
HTTP://WWW.KMART.COM.AU



INSTRUCTIONS FOR USE AND CARE

LIGHTWEIGHT CYCLE HELMETS

DESIGNED TO MEET ALL TESTING REQUIREMENTS OF:
AUSTRALIA / NEW ZEALAND
AS/NZS 2063: 2008



Australian /
New Zealand Standard
AS/NZS 2063:2008
Bicycle helmets
Lic No. SMK02623.
SAI GLOBAL

WARNING

1. This helmet conforms to the AS/NZS 2063:2008 standard for bicycle helmets. It designed for use with pedal cycles, skateboards and kick scooters, not intended for motorsport use.

2. No Helmet can protect the wearer against all possible impacts.

3. The helmet is designed to be retained by a strap under the lower jaw.

4. To Be effective, a helmet must fit and be worn correctly. To check for correct fit, place helmet on head and make any adjustments indicated. Securely fasten retention system. Grasp the helmet and try to rotate it to the front and rear. A correctly fitted helmet should be comfortable and should not move forward to obscure vision or backwards to expose the forehead.

5. No Attachments should be made to the helmet except those recommended by the helmet manufacturer.

6. The helmet is designed to absorb shock by partial destruction of the shell and liner. This damage may not be visible. Therefore, if subjected to severe blow, the helmet should be destroyed and replaced even if it appears undamaged.


7. The helmet may be damaged and rendered ineffective by petroleum and petroleum products, cleaning agents, paints, adhesives and the like, without the damage being visible to the user.

8. A helmet has a limited lifespan in use and should be replaced when it shows obvious signs of wear.

9. This helmet should not be used by children while climbing or doing other activities where there is a risk of hanging or strangulation if the child gets trapped whilst wearing the helmet.

THE PROPER FIT

STEP 1: The helmet fits correctly when the fit pads hold it firmly but comfortably in place. Pads are held in place by hook and loop style fastener. All fitting adjustments **MUST** be made with the helmet in the proper position. Failure to do so will result in a poor fit. This will allow the helmet to move out of position or come off in an accident. For proper position, please refer to Diagram A.




STEP 2: Always wear a helmet low in the front to protect the forehead as in the correct figure in Diagram A


STEP 3: The front and rear straps should join at a point slightly below and in front of the ears. See Diagram B. To adjust the position of the straps hold one end of the buckle in one hand and slide the adjuster up or down as necessary with the other hand correctly positioned to adjust the front or rear strap individually. Hold the strap to be adjusted and slide the slide adjuster in the appropriate direction.



STEP 4: Always wear the helmet with the chin strap buckle fastened and the strap pulled tight. Make sure the strap is well back against the throat, **NOT** on the point of the chin. Straps worn on the point of the chin increase the chance of the helmet coming off in an accident. See Diagram C and Diagram D on how to fasten and release the buckle and Diagram E shows the proper placement of the chin strap.



Make sure the loose end of the strap passes through the rubber O ring. If it does not, the strap may slide loose and the helmet can come off accidentally. See Diagram F



STEP 5: Before using the helmet, make sure it fits correctly, the straps are correctly adjusted and the chin strap is tight enough. Put the helmet on in the correct position. Fasten the chin strap and pull it tight.

STEP 6: Once you are satisfied that the helmet fits correctly and all straps are properly adjusted and tightened, take a short ride. Pay attention to overall comfort and helmet stability while riding. Make any minor adjustment to fit pads and straps to improve the comfort stability.