

# INSTRUCTION MANUAL

**Consult a DIY expert if you need advice on how to lay these tiles correctly.**

## Recommended Surfaces:

These surfaces will provide good quality results:

1. Smooth concrete floor;
2. Smooth marble floor;
3. Smooth solid wood floor;
4. Wood-plastic composite floor;

## Non-Recommended Surfaces:

These surfaces will not be suitable for use:

1. Floating floorboards;
2. Asphalt or thermoplastic floor;
3. Oily floor;
4. Embossed elastic floor or cushioning floor.

## Before you start:

1. Before installation, carefully check whether the floor tile has any defects and adhesive protection has not been removed
2. The floor tile should best be kept at room temperature 12°C - 29°C 48 hours before installation. If the tiles have been stored correctly, the tiles need no further adjustment and can be used directly from the packaging.
3. Before laying floor tiles, please ensure that the floor is smooth, clean and dry, and there is no wax, grease, oil and dust. Floors can be covered with latex primer and a moisture-proof film added if required. New concrete flooring should be dried for at least 60 days before installation.
4. Porous surface, such as sand and cement screed, plywood, cardboard and particleboard, the application of an appropriate primer sealant before installation; such as a latex primer.

## Installation:

1. Begin laying your floor at the corner of the longest wall.
2. Position at your starting point. Check that this position is correct and apply firm pressure all over to achieve complete contact. Lay all full tiles ensuring a close fit but do not force together.
3. When you reach the final row, cut the last tile to fit.

## Ongoing Care & Cleaning

1. Use door mats at the entrance to prevent fading of floor tiles. Avoid rubber-padded carpets as they may stain or discolor the vinyl flooring. If your driveway is asphalt, use a sturdy door

mat at your gate, as chemicals in asphalt can cause vinyl flooring to turn yellow.

2. After laying the floor tiles, check whether all the floor tiles on the floor are firmly stuck, before cleaning the floor, set aside 5-7 days of time, this is to let the tile adhesion on the bottom floor.
3. Try not to make the floor too wet when cleaning. It is recommended to wipe it with a damp cloth.
4. Other precautions: Stilettos can damage floors. Use protective pads under furniture.

Removal:

- Start in a corner, then slowly and gently peel away like a sticker

WARNING: TEST IN AN INCONSPICUOUS LOCATION AND CHECK AFTER 7 DAYS FOR SUITABILITY OF SURFACE. WHILE THIS TILE HAS BEEN TESTED ON THE RECOMMENDED SURFACES IN VARYING CONDITIONS, WE CANNOT GUARANTEE THAT UNDER ALL CIRCUMSTANCES THE MATERIAL WILL STAY COMPLETELY INTACT, THAT THE PRODUCT WILL PROPERLY ADHERE TO THE SURFACE OR THAT NO ADHESIVE WILL REMAIN ON THE SURFACE WHEN REMOVED. THE PERFORMANCE OF THE PRODUCT MAY BE AFFECTED BY:

- THE NUMBER OF COATS OF PAINT ON THE SURFACE
- THE AGE AND TYPE OF PAINT USED
- BUMPS AND CRACKS ON THE SURFACE
- DRYNESS OR DAMPNESS OF THE SURFACE
- HEAT FROM DIRECT SUNLIGHT